

Multichannel LVDT Signal Conditioner Supports Position Measurement Applications

SAN DIEGO, Calif.—June 12, 2007—ACCES I/O Products Inc., introduces its newly designed LVDT signal conditioner board, Model LVDT-8A. This user-friendly board offers any position measurement requirement a simple, accurate, and easy-to-use solution at a great price. Eight channels of signal conditioning on one board results in a price per channel of under \$100. The elimination of multiplexer circuitry on the board provides enhanced capability of simultaneous outputs that directly correspond to the sensed positions in a real-time environment. Removable screw-terminal blocks are used on the LVDT-8A board to allow convenient connection to linear variable differential transformers (LVDTs) through screw terminals. Use of five on-board LEDs verifies the full voltage range of the LVDT providing validation of functionality and input circuit connection. ACCES has designed the LVDT-8A to be the ideal signal conditioner for use in factory automation environments such as automotive, machining, inspection, weighing and process control.

The board is packaged in a rugged industrial enclosure that offers physical protection and features a DIN rail-mounting provision for industrial environments. Accessories include an assortment of 37-pin ribbon cables for connecting the conditioned outputs to a variety of readily available analog-to-digital converter products. ACCES offers a broad range of A/D products using USB, RS-485, PCI, PC/104, Ethernet, 900MHz/2.4GHz wireless and even ISA bus types.

Key features include:

- Eight channels of AC LVDT conditioning
- Removable screw-terminal blocks for easy connection and serviceability
- Use easily with PLC or PC-based data acquisition systems
- Real-time, simultaneous outputs
- Compatible with other ACCES A/D products for legacy systems using DB37M
- LED display utility for quick and easy verification of connected LVDTs
- Factory-set oscillator frequency per channel from 20Hz to 20KHz
- ± 10 VDC or ± 5 VDC outputs including wide range calibration pots
- Excellent temperature stability
- Operates on 24VDC power, factory options for 12VDC, ±12VDC or 48VDC
- Reverse input power protection to eliminate misconnection worries
- Includes rugged, industrial enclosure for physical protection and mounting
- DIN rail-mounting provision

No software is necessary to start using the LVDT-8A. It can be utilized right out of the box. A user friendly setup program and user manual is included with each shipment. The setup program can be used to help with the selection of application-specific options and the user manual contains full details on the board's operation.

ACCES I/O Products, Inc. supplies an extensive range of analog, digital, serial communication, and isolated I/O boards and solutions. ACCES also offers complete systems, integration services and enclosures with a quick turn-around on custom projects including software. ACCES products are designed for use with PC/104, PCI, PCI-X, Low Profile PCI, EBX, ETX, EPIC, USB, Ethernet and ISA, as well as distributed and wireless I/O. All hardware comes with a 30-day, no-risk return policy and a three-year warranty. For further information, visit the company's web site at <u>www.accesio.com</u>.

Price: \$795.00—LVDT-8A eight-channel LVDT signal conditioner in enclosure (Volume pricing available, consult factory)


Availability: Now

Delivery: Stock to two weeks ARO

For Further Information, Contact:

Chris Persidok, Marketing Manager ACCES I/O Products, Inc. 10623 Roselle Street, San Diego, CA 92121 Tel: 858.550.9559 • FAX: 858.550.7322 E-mail: <u>cpersidok@accesio.com</u> URL: <u>www.accesio.com</u> Agency Contact:

Mike Gerow, PR Director WelComm, Inc. *B2B Marcom Experts* 7975 Raytheon Rd., Suite 340, San Diego, CA 92111 858.279.2100 FAX: 858.279.5400 E-mail: <u>mike@welcomm.com</u>



Multichannel LVDT Signal Conditioner Supports Position Measurement Applications (Model LVDT-8A)

